WASHER & DRYER Forever machine



352GAU
[CAPACITY]
35.2kg

272GAU
[CAPACITY]
27.3 kg

352SAU
[CAPACITY]
35.2kg

272SAU
[CAPACITY]
27.3kg

Reduced operating costs can be achieved using the 10 available water level settings





WUD272GAU [CAPACITY] 27.3KG

WUD272SAU (CAPACITY) 27.3KG

WUD352GAU

WUD352SAU [CAPACITY] 35.2KG

No.1 ranked dehydration efficiency

High Dehydration efficiency is possible because of our unique high speed soft mount design, equals reduced drying time and savings on your gas bill.

Installation space can be reduced to half

Washing and drying can be completed with one unit and effective use of facility limited space can be ensured.

8 different types of auxiliary agents (liquid) can be charged

Eight different types of auxiliary agents (liquid) can be charged automatically by the set amount. Correct chemical dosage is achieved on every load. (dosing pump is optional)

SPECIFICATION

WASHER & DRYER WUD SERIES

| Gas heated model | | WUD272GAU | WUD352GAU |
|------------------------|--------------------|-----------------------|-----------------------|
| Capacity | Wash only | 27.3kg | 35.2kg |
| | Dry to Dry | 17kg | 24kg |
| Drum | Diameter | 762mm | 890mm |
| | Depth | 600mm | 566mm |
| Speed | Wash | 20-50rpm | 20-50rpm |
| | Extract | 100-880rpm | 100-800rpm |
| Power supply | | AC415V 3-Phase 4-wire | AC415V 3-Phase 4-wire |
| Motor | | 4.0Kw 4P | 5.5Kw 4P |
| Gas Supply pressure | Water | 0.1-0.3MPa | 0.1-0.3MPa |
| | Hot water | 0.1-0.3MPa | 0.1-0.3MPa |
| | Natural gas/LP gas | 1.15kPa / 2.75kPa | 1.15kPa / 2.75kPa |
| Machine weight | | 890kg | 1,140kg |

| Steam heated model | | WUD272SAU | WUD352SAU |
|--------------------|------------------------------|-----------------------|-----------------------|
| Capacity | Wash only | 27.3kg | 35.2kg |
| Сарасіту | Harmony load (dry to dry) | 11kg | 15kg |
| Drum | Diameter | 762mm | 890mm |
| Didili | Depth | 486mm | 566mm |
| Speed | Wash | 20-50rpm | 20-50rpm |
| Speed | Extract | 100-880rpm | 100-800rpm |
| Power supply | | AC415V 3-Phase 4-wire | AC415V 3-Phase 4-wire |
| Motor | | 4.0Kw 4P | 5.5Kw 4P |
| | Water | 0.1-0.3MPa | 0.1-0.3MPa |
| Supply | Hot water | 0.1-0.3MPa | 0.1-0.3MPa |
| | Steam | 0.4-0.6MPa | 0.4-0.6MPa |
| Machine weight | | 890kg | 1,140kg |

DIMENSION WUD272GAU WUD272SAU 1012 1389 1012 1374 1848 1848 Front side view Front side view Left side view Left side view WUD352GAU WUD352SAU 1442 1440 1148 1148 1958 1958 Front side view Left side view Front side view Left side view